FLEXIBILITY FOR BETTER BUSINESS PRINT MANAGEMENT.

Get fully flexible and customisable printing solutions for your business with the EcoTank L15180 colour printer. Powered by Heat-Free Technology, this printer increases productivity with ultra-high page yield and consistent high-speed printing of up to 25 ipm. Printouts are sharp, crisp and water-resistant from our 4-colour pigment ink which is suitable for business printing. Secure the access of your devices through authentication and leverage control to reduce cost of printing.

UP TO 25 IPM — ISO Print Speed

Duplex Printing

A3+ — Prints in up to A3+*

Ethernet

WiFi Direct

Epson Connect

Open Platform Enabled

Space Saving

ecotank

PRECISIONCORE HEAT-FREE

India's No.1 INKJET PRINTER

DURABrite ET INK

Built for Business
Improve productivity with ultra-high page yield and consistent fast print speed of up to 25 ipm, delivering prints of impeccable quality from our 4-colour pigment ink.

Open Platform-enabled
Manage your printers with Epson Print Admin or integrate with compatible third party print management solutions.

Heat-Free Technology
Enjoy high-speed printing with minimal power consumption via Epson's Heat-Free Technology.

*For simplex only. #Source: IDC Asia Pacific Hardcopy Peripheral Tracker FY2021 H1. Volume Market Share of A4 Inkjet Printers and MFPs.

SPECIFICATIONS
ECOTANK L15180

Model Number	**L15180**
Printer Type	Print, Scan, Copy and Fax with ADF

Printing

Printing Technology	PrecisionCore™ Printhead
Nozzle Configuration	800 x 1 nozzles each (Black, Cyan, Magenta, Yellow)
Print Direction	Bi-directional printing
Maximum Resolution	4800 x 1200 dpi
Minimum Ink Droplet Volume	3.8 pl
Print Speed[*1]	
Draft Text - Memo, A4 (Black[#1] / Colour[#2])	Up to 32 ppm / 32 ppm
ISO 24734, A4 (Black / Colour)	Simplex: Up to 25 ipm / 25 ipm | Duplex: Up to 21 ipm / 21 ipm
ISO 24734, A3 (Black / Colour)	Simplex: Up to 13.5 ipm / 13.5 ipm | Duplex: Up to 10 ipm / 10 ipm
First Page Out Time A4 (Black / Colour)	Simplex: Up to 5.5 sec / 5.5 sec | Duplex: Up to 11.0 sec / 11.5 sec
Photo Default[*2] - 10 x 15 cm / 4 x 6"[#3] (Border / Borderless)	Approx. 26 sec per photo / 27 sec per photo
Printer Language	ESC/P-R
Emulation	PCL5 / PCL6 / PostScript3 / PDF (ver1.7)
Automatic 2-sided printing	Yes (up to A3)

Copying

Copy Speed	
ISO 29183, A4 (Black / Colour), Flatbed	Simplex: Up to 23 ipm / 23 ipm
ISO 24735, A4 (Black / Colour), ADF	Simplex: Up to 22.5 ipm / 22.5 ipm | Duplex: Up to 19 ipm / 19 ipm
Maximum Copies from Standalone	999 copies
Reduction / Enlargement	25 - 400%, Auto Fit Function
Maximum Copy Resolution	600 x 600 dpi
Maximum Copy Size	A3

Scanning

Scanner Type	Flatbed colour image scanner
Sensor Type	CIS
Optical Resolution	1200 x 2400 dpi
Maximum Scan Area	297 x 431.8 mm
Scanner Bit Depth	
Colour	48-bit input, 24-bit output
Grayscale	16-bit input, 8-bit output
Black & White	16-bit input, 1-bit output
Scan Features	Scan to Memory Device, Scan to Network Folder / FTP, Scan to Email, Scan to Computer (Epson ScanSmart), Scan to Computer (WSD)
Scan Speed (Flatbed / ADF (Simplex) / ADF (Duplex))	
Monochrome 200 dpi	Flatbed: 5 sec, ADF (Simplex / Duplex): Up to 26.0 ipm / 11.5 ipm
Colour 200 dpi	Flatbed: 10 sec, ADF (Simplex / Duplex): Up to 9.0 ipm / 6.0 ipm

Fax Function

Type of Fax	Walk-up black-and-white and colour fax capability
Receive Memory / Page Memory	6MB, Up to 550 pages (ITU-T No.1 chart)
Error Correction Mode	ITU-T T.30
Fax Speed (Data Transfer Rate)	Up to 33.6 kbps, Approx. 3 sec/page
Fax Resolution	Up to 200 x 200 dpi
Transmission Paper Size	
Flatbed	A5, A4, A3, B5, B4, Half Letter, Letter, Legal, 27.94 x 43.18 cm (11 x 17")
ADF	A5, A4, A3, B5, B4, Half Letter, Letter, Legal, 27.94 x 43.18 cm (11 x 17")
Receiving Paper Size	Half Letter, A5, B5, A4, Letter, Legal, B4, 27.94 x 43.18 cm (11 x 17"), A3, A3+
Speed Dial / Group Dial	Up to 200 numbers, 199 groups
Fax Features	PC Fax (Transmission / Receive), Automatic Redial, Address Book, Transmit Reservation, Broadcast Fax (Mono only), Polling Reception, Fax Preview, Fax to E-mail, Memory Reception, Fax to Folder, Automatic 2-sided Fax

ADF Function

Support Paper Thickness	64-95 g/m²
Paper Capacity	50 pages (80 g/m²)

Card Slot / USB Host Function

USB Host	USB Host (Scan to memory device / Storage function)
Direct Print Paper Size	A6, A5, A4, A3, A3+, B6, B5, B4, 10 x 15 cm, 16:9 wide, 13 x 18 cm, #10, DL, C6, C4, 16K, Indian-Legal, Letter, 8.5 x 13", Legal, 8K
Supported Formats (Direct Print)	JPEG, TIFF, PDF

Paper Handling

Paper Feed Method	Friction feed
Number of Paper Trays	3 (Front 2, Rear 1)
Paper Hold Capacity	
Input Capacity	Cassette 1: 250 sheets (80 g/m²), 50 sheets of Premium Glossy Photo Paper Cassette 2: 250 sheets (80 g/m²) Rear Tray: 50 sheets (80 g/m²), 20 sheets of Premium Glossy Photo Paper
Output Capacity	125 sheets (80 g/m²), 20 sheets of Premium Glossy Photo Paper
Paper Size	A6, A5, A4, B6, B5, Indian-Legal, Letter, Executive, 16K, Indian-Legal, Letter, 21.6 x 33 cm (8.5 x 13"), Legal 8.5 x 14" (21.6 x 35.6 cm), 10.1 x 15.2 cm (4 x 6"), 12.7 x 17.8 cm (5 x 7"), 20.3 x 25.4 cm (8 x 10"), 16:9 wide, Envelopes #10, DL, C6, C4
Maximum Paper Size	21.6 x 600 cm (8.5 x 236.2")
Print Margin	0 mm top, left, right, bottom via custom settings in printer driver (except plain paper)[*3]

Interface

USB	USB 2.0
Network	Ethernet, WiFi IEEE 802.11b/g/n, WiFi Direct (8 connections)
Network Protocol	TCP/IPv4, TCP/IPv6, LPD, IPP, PORT9100, WSD
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD
Security Functions	Limit Access Function, PIN No. Certification, LDAP Address Book, IP Address Filtering, Panel Admin Mode
Epson Open Platform	Yes

Mobile and Cloud Printing

Epson Connect	Epson Smart Panel, Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud
Other Mobile Solutions	Apple AirPrint, Mopria Print Service

Control Panel

LCD Screen	10.9 cm (4.3") TFT Colour Touch LCD

Printer Software

Software Support	Epson ScanSmart (Win / Mac)
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Mac OS X 10.6.8 or later

Electrical Specifications

Rated Voltage	AC 220 - 240 V
Rated Frequency	50 - 60 Hz
Power Consumption	
Operating	20 W
Standby	10.3 W
Sleep	0.9 W
Power Off	0.2 W
Typical Electricity Consumption (TEC) Number	0.15 kWh

Noise Level

PC Printing / Colour	6.7B(A), 52dB(A)
PC Printing / Black	6.7B(A), 52dB(A)

Dimensions & Weight

L15180
Weight: 21.0 kg

350 mm (13.8")
515 mm (20.3")
500 mm (19.7")

#1	#2	#3
Black Text	Colour	Photo 4R

Dealer's Stamp